

LASAGGREGAAT MSG CHOPPER

- DC lasaggregaat
- Hulpstroom 2 kW gelijkstroom
- Draagbaar (28,5 kg)
- Twee takt benzinemotor
- Stationairautomaat
- Inclusief laskabelset



Standaard uitrusting



Gasoline engine	Air cooling	Manual recoil	Welding cables						
Generator high frequency	Socket 230V EEC	Fuse							

Opties

- Inductance to improve welding performance RL1



Technische gegevens MSG CHOPPER

D.C. LASSEN

Current range, continuous	50 - 165 A
Open circuit voltage	50 V
Duty cycle	165 A - 35%, 140 A - 60%
Electrode diameter	2 - 4 mm

D.C. GENERATOR

High frequency, self-excited, brushless

Single-phase generation	2 kW / 230 V / 8.7 A
Duty cycle	100%
Insulating class	H

MOTOR

Gasoline, 2-stroke, air cooled

Type	MOSA
Output *	6.6 kW (9 HP)
Speed	6000 rpm
Displacement / Cylinders	125 cm ³ /1
Fuel system	gasoline/oil mixture (50 : 1)
Fuel consumption	530 g/kWh

* Maximum output (not overloadable) according to ISO 3046/1

ALGEMENE SPECIFICATIES

Tank capacity	3 l
Running time (at duty cycle 60%)	1.5 h
Protection	IP 23
Dimensions Lxwxh (mm)	570x300x410
Weight	28.5 kg
Noise level	101 LWA(76 dB(A) - 7 m)

Model- en specificatiewijzigingen voorbehouden