

LASAGGREGAAT TS 250 SC/EL - SXC/EL

- Electronische lasstroom regeling
- Afstandbediening (optie)
- Hulpstroom (9 kVA) beschikbaar tijdens lassen
- Aardlekschakelaar
- Moderne zuinige dieselmotor
- Motorbeveiliging (oliedruk/temperatuur)
- Onderstel (optioneel)
- Voldoet aan de EG veiligheids- en geluidsnormen



Standaard uitrusting



Diesel engine	Air cooling	Electric starter	Battery 12V	Battery charger indicator	Hour Meter	Engine protection	Low oil pressure	Low fuel	High oil temperature	Central lifting eye
Welding current electr. regulation	Asynchronous alternator	Voltmeter	Ground fault interrupter	Socket 400V EEC	Socket 230V EEC	Fuse	Ready for TC			

Opties



- Plug 400V 32A 3PNT (T)
- Plug 230V 32A or 16A 2PT (M)
- Plug 110V 32A or 16A 2PT (M)
- Arc control Kit
- Welding cables K200 (20+15m, 35mm²)
- Remote control TC2 with cable 20m
- Remote control TC2/50 with cable 50m
- Earthing kit MT10
- Trolley CTM300
- Site tow CTL300
- Road tow CTV3

Technische gegevens

TS 250 SC/EL

TS 250 SXC/EL

D.C. LASSEN

Current range, continuous	20 - 250 A
Open circuit voltage	70 V
Duty cycle	250 A - 60%, 200 A - 100%
Electrode diameter	2 - 6 mm

A.C. GENERATOR

50 Hz, asynchronous, three-phase, self-excited, self-regulated, brushless

Three-phase generation	9 kVA / 400 V / 13 A
Single-phase generation	5 kVA / 230 V / 21.7 A
Single-phase generation (option)	2.5 kVA / 110 V / 22.7 A
Single-phase generation (option)	5 kVA / 48 V / 104 A
Duty cycle	100%
Insulating class	H

On request other voltages and frequencies (60 Hz)

MOTOR

Diesel, 4-stroke, air cooled

Type	Ruggerini RD 210
Output *	14 kW (19 HP)
Speed	3000 rpm
Displacement	954 cm ³
Cylinders	2
Fuel consumption	250 g/kWh

* Maximum output (not overloadable) according to ISO 3046/1

ALGEMENE SPECIFICATIES

Tank capacity	23 l
Running time (at duty cycle 60%)	11 h
Protection	IP 23
Dimensions * Lxwxh (mm)	1320x790x750
Weight *	325 kg
Noise level	99 LWA(74 dB(A) - 7 m)
	340 kg
	93 LWA(68 dB(A) - 7 m)

* Dimensions and weight are inclusive of all parts without wheels and towbar

Model- en specificatiewijzigingen voorbehouden