

LASAGGREGAAT TS 400 SC -SXC/EL

- Electronische lasstroom regeling
- Arc control voor cellulose elektroden
- Hulpstroom (13 kVA) beschikbaar tijdens lassen
- Aardlekschakelaar
- Moderne zuinige dieselmotor
- Motorbeveiliging (oliedruk/temperatuur)
- Onderstel (optioneel)
- Voldoet aan de EG veiligheids- en geluidsnormen



Standaard uitrusting											
	Diesel engine	Air cooling	Electric starter	Battery 12V	Battery charger indicator	Hour Meter	Engine protection	Low fuel	High oil temperature	Oil pressure	Central lifting eye
Opties											
	Welding current electr. regulation	Arc force	Asynchronous alternator	Ground fault interrupter	Socket 400V EEC	Socket 230V EEC	Fuse	Voltmeter	Ready for TC		
	● Plug 400V or 230V 32A 3PNT (T)				● Welding cables K400 (20+15m, 50mm ²)						● Site tow CTL400
	● Plug 230V 32A 2PT (M)				● Remote control TC2 with cable 20m						● Road tow CTV3
					● Remote control TC2/50 with cable 50m						● Earthing kit MT10

- Uitvoering Op verzoek**
- Engine protection and economizer EP1 (Auto Idle), only for SX Version
 - Other Voltage (110V or 48V)

Technische gegevens	TS 400 SC/EL	TS 400 SXC/EL
D.C. Lassen		
Current range, continuous	20 - 400 A	20 - 400 A
Open circuit voltage	70 V	70 V
Duty cycle	400 A-35%, 350 A-60%, 300 A-100%	400 A-35%, 350 A-60%, 300 A-100%
Electrode diameter	2 - 8 mm	2 - 8 mm
A.C. GENERATOR 50 Hz, asynchronous, three-phase, self-excited, self-regulated, brushless		
Three-phase generation	13 kVA / 400 V / 18.7 A	13 kVA / 400 V / 18.7 A
Single-phase generation	7 kVA / 230 V / 30.4 A	7 kVA / 230 V / 30.4 A
Single-phase generation (option)	3.5 kVA / 110 V / 31.8 A	3.5 kVA / 110 V / 31.8 A
Single-phase generation (option)	5 kVA / 48 V / 104 A	5 kVA / 48 V / 104 A
Duty cycle	100%	100%
Insulating class	H	H
Motor Diesel, 4-stroke, air cooled		
Type	Lombardini 9LD625/2	Lombardini 9LD625/2
Output *	19.1 kW (26 HP)	19.1 kW (26 HP)
Speed	3000 rpm	3000 rpm
Displacement	1250 cm ³	1250 cm ³
Cylinders	2	2
Fuel consumption	250 g/kWh	250 g/kWh

* Maximum output (not overloadable) according to ISO 3046/1

ALGEMENE SPECIFICATIES		
Tank capacity	26 l	26 l
Running time (at duty cycle 60%)	8 h	8 h
Protection	IP 23	IP 23
Dimensions * Lxwxh (mm)	1455x870x880	1455x870x880
Weight *	450 kg	465 kg
Noise level	98 LWA (73 dB(A) - 7 m)	93 LWA (68 dB(A) - 7 m)

* Dimensions and weight are inclusive of all parts without wheels and towbar

Model- en specificatiewijzigingen voorbehouden