

STROOMAGGREGAAT GE 12000 SXC/GS EAS

- Dieselmotor - 3000 rpm
- ES motorbewaking
- Enkelfase synchrone generator
- Uitgangen 230V: 1 x 230V 63A 2P+T CEE
1 x 230V 32A 2P+T CEE - 1 x 230V 16A 2P+T CEE
- Uitgangen 230V/115V : 1 x 230V 32A 2P+T
1 x 230V 16A 2P+T
2 x 115V 32A 2P+T - 2 x 115V 16A 2P+T
- ELCB-GFI (aardlekschakelaar)
- Zekeringautomaat
- Super geluidgedempt
- Onderstel (optie)
- Uitermate geschikt voor toepassing waar veel power 230V nodig is
- Compact, robuust, ideaal voor aannemerij



Standard Equipment											
	Diesel engine	Air cooling	Electric Starter	Battery 12 V	Engine protection	Oil pressure shut down	High temp. engine shut down	Battery charge indicator	Low fuel indicator	Hour-meter	Central lifting eye
Opties											
	Synchronous alternator	Sockets	ELCB-GFI	Circuit Breaker	Thermal shut off	Voltmeter Frequency -meter	Ready for EAS/TCM	Local/remote start selector			
Opties af fabriek	● 230V plugs ● 115V plugs ● Earthing kit			● Remote control (EAS Version) ● Automatic transfer unit (AMF) EAS 17M-805 ● Tank locking cap				● Trolley CTM300 ● Site tow CTL300 ● Road trolley CTV4			
	● Oil heater OH										

Technische gegevens

GE 12000 SXC/GS EAS

A.C GENERATOR – 50 Hz

Single-phase synchronous alternator, self-excited, self-regulated, brushless

* Stand-by single-phase power	13.5 kVA (12.1 kW) / 230 V / 58.7 A
* P.R.P. single-phase power	12 kVA (10.8 kW) / 230 V / 52.5 A
* Stand-by single-phase power (115V)	13.5 kVA (12.1 kW) / 115 V / 117.4 A
* P.R.P. single-phase power (115V)	12 kVA (10.8 kW) / 115 V / 104.3 A
Cos φ	0.9
Insulation class	H

* Output powers according to ISO 8528-1

MOTOR

4-stroke diesel, air cooled, direct injection

Model	Lombardini 12LD 477/2
* Stand-By net power	14.9 kW (20.3 HP)
* P.R.P. net power	13.5 kW (18.4 HP)
Cylinders/ Displacement	2 / 954 cm ³
Speed	3000 rpm
Fuel consumption (75% of P.R.P)	2.8 l/h

* Powers according to ISO 3046-1

ALGEMENE SPECIFICATIES

Tank capacity	23 l
Running time (75% of P.R.P)	8.2 h
IP protection degree	IP 23
*Dimensions LxWxh (mm)	1320x790x750 mm
*Dry weight	297 kg
**Measured acoustic power LwA (pressure LpA)	96 dB(A) (71 dB(A) @ 7m)
**Guaranteed acoustic power LwA (pressure LpA)	96 dB(A) (71 dB(A) @ 7m)

* Dimensions and weight without trolley/trailer. ** Acoustic power according to European Directive 2000/14/EC