

## STROOMAGGREGAAT GE 13000 SC / SXC - SXC EAS

- Diesel motor - 3000 rpm
- ES motorbewaking
- Driefase asynchrone generator
- Uitgangen: 1 x 400V 32A 3P+N+T CEE  
2 x 230V 32A 2P+T CEE
- ELCB-GFI (aardlekschakelaar)
- Geschikt voor o.a. elektronische apparatuur
- Geluidgedempt (SXC)
- Onderstel (optie)
- Voorbereid door aansluiting noodstroomunit (SXC EAS)
- Voldoet aan de EG veiligheids- en geluidsnormen



Standaard uitrusting											
	Diesel engine	Air cooling	Electric Starter	Battery 12 V	Engine protection	Oil pressure shut down	High temp. engine shut down	Battery charge indicator	Low fuel indicator	Hour-meter	Central lifting eye
Opties										*only SXC EAS	
	Asynchronous alternator	Sockets 3~	Sockets 1~	ELCB-GFI	Fuse	Voltmeter	Ready for EAS/TCM *	local/remote start selector *			
	<ul style="list-style-type: none"> <li>● 400V plug</li> <li>● 230V plug</li> <li>● Earthing kit</li> </ul>				<ul style="list-style-type: none"> <li>● Remote control</li> <li>● Automatic transfer unit (AMF) EAS 17-805</li> <li>● Tank locking cap</li> </ul>				<ul style="list-style-type: none"> <li>● Trolley CTM300</li> <li>● Site tow CTL300</li> <li>● Road trolley CTV4</li> </ul>		

Opties, af fabriek ● Oil heater OH

### Technische gegevens GE 13000 SC GE 13000 SXC GE 13000 SXC EAS

<b>A.C GENERATOR – 50 Hz</b>	<b>Three-phase asynchronous alternator, self-excited, self-regulated, brushless</b>
* Stand-by three-phase power	14.5 kVA (11.6 kW) / 400 V / 20.9 A
* P.R.P. three-phase power	13 kVA (10.4 kW) / 400 V / 18.8 A
* P.R.P. single-phase power	10 kVA / 230 V / 43.5 A
Cos φ	0.8
Insulation class	H
* Output powers according to ISO 8528-1	

<b>MOTOR</b>	<b>4-stroke diesel, air cooled, direct injection</b>
Model	Lombardini 12LD 477/2
* Stand-By net power	14.9 kW (20.3 HP)
* P.R.P. net power	13.5 kW (18.4 HP)
Cylinders/ Displacement	?2/ 954 cm <sup>3</sup>
Speed	3000 rpm
Fuel consumption (75% of P.R.P.)	2.8 l/h
* Powers according to ISO 3046-1	

<b>ALGEMENE SPECIFICATIES</b>	
Tank capacity	23 l
Running time (75% of P.R.P.)	8.2 h
IP protection degree	IP 23
*Dimensions LxWxh (mm)	1320x790x750 mm
*Dry weight	340 kg 360 kg
**Measured acoustic power LwA (pressure LpA)	96 dB(A)(71 dB(A) @ 7m)
**Guaranteed acoustic power LwA (pressure LpA)	96 dB(A)(71 dB(A) @ 7m)
***Acoustic power LwA (pressure LpA)	98 dB(A) (73 dB(A) @ 7 m)
* Dimensions and weight without trolley/trailer. ** Acoustic power according to European Directive 2000/14/EC	
***For indoor use / For fixed installation only, in compliance with Directive 2000/14/EC	

Model- en specificatiewijzigingen voorbehouden