

STROOMAGGREGAAT GE 14000 SXC/GS EAS

- Dieselmotor - 3000 rpm
- ES motorbewaking
- Driefase synchrone generator
- Uitgangen : 1 x 400V 32A 3P+N+T CEE - 1 x 400V 16A 3P+N+T CEE
1 x 230V 32A 2P+T CEE - 1 x 230V 16A 2P+T CEE
- ELCB-GFI (aardlekschakelaar)
- Zekeringautomaat
- Super geluidgedempt
- Onderstel (optie)
- Voorbereid voor noodstroom en start/stop op afstand
- Voldoet aan de EG veiligheids- en geluidsnormen



Standaard uitrusting											
	Diesel engine	Air cooling	Electric Starter	Battery 12 V	Engine protection	Oil pressure shut down	High temp. engine shut down	Battery charge indicator	Low fuel indicator	Hour-meter	Central lifting eye
Opties											
	Synchronous alternator	Compound	Sockets 3~	Sockets 1~	ELCB-GFI	Circuit Breaker	Voltmeter Frequency-meter	Ready for EAS/TCM	Local/remote start selector		
Opties af fabriek	<ul style="list-style-type: none"> ● 400V plug ● 230V plug ● Earthing kit ● Automatic transfer unit (AMF) EAS 17-805 ● Remote control ● Tank locking cap ● Trolley CTM300 ● Site tow CTL300 ● Road trolley CTV4 ● Oil heater OH 										

Technische gegevens

GE 14000 SXC/GS EAS

A.C GENERATOR – 50 Hz	Three-phase synchronous alternator, self-excited, self-regulated
* Stand-by three-phase power	15 kVA (12 kW) / 400 V / 21.7 A
* P.R.P. three-phase power	13.5 kVA (10.8 kW) / 400 V / 19.5 A
* P.R.P. single-phase power	5 kVA / 230 V / 21.7 A
Cosφ	0.8
Insulating class	H
* Output powers according to ISO 8528-1	
MOTOR	4-stroke diesel, air cooled, direct injection
Model	Lombardini 12LD 477/2
* Stand-By net power	14.9 kW (20.3 HP)
* P.R.P. net power	13.5 kW (18.4 HP)
Cylinders/ Displacement	2 / 954 cm ³
Speed	3000 rpm
Fuel consumption (75% of P.R.P.)	2.8 l/h
* Powers according to ISO 3046-1	

ALGEMENE SPECIFICATIES	
Tank capacity	23 l
Running time (75% of P.R.P.)	8.2 h
IP protection degree	IP 23
*Dimensions LxWxh (mm)	1320x790x750 mm
*Dry weight	315 kg
**Measured acoustic power LwA (pressure LpA)	96 db(A) (71 dB(A) @ 7m)
**Guaranteed acoustic power LwA (pressure LpA)	96 db(A) (71 dB(A) @ 7m)
* Dimensions and weight without trolley/trailer. ** Acoustic power according to European Directive 2000/14/EC	

Model- en specificatiewijzigingen voorbehouden