

STROOMAGGREGAAT GE 15000 SC / SXC - SXC EAS

- Diesel motor -3000 rpm
- ES motorbewaking
- Driefase asynchrone generator
- Uitgangen: 1 x 400V 32A 3P+N+T CEE
2 x 230V 32A 2P+T CEE
- ELCB-GFI (aardlekschakelaar)
- Geschikt voor o.a. elektronische apparatuur
- Super geluidgedempt (SXC)
- Onderstel (optie)
- Voorbereid voor aansluiten EAS noodstroomunit
- Voldoet aan de EG veiligheids- en geluidsnormen



| | | | | | | | | | | | |
|-------------------------|--|-------------|--|-------------|-------------------|------------------------|--|-------------------------------|--------------------|------------|---------------------|
| Standaard uitrusting | | | | | | | | | | | |
| | Diesel engine | Air cooling | Electric Starter | Battery 12V | Engine protection | Oil pressure shut down | High temp. engine shut down | Battery charge indicator | Low fuel indicator | Hour meter | Central lifting eye |
| Opties | | | | | | | | | | | |
| | Asynchronous alternator | Sockets 3~ | Sockets 1~ | ELCB-GFI | Thermal shut off | Voltmeter | Ready for EAS/TCM * | Local/Remote Start selector * | | | |
| Opties, af fabriek | <ul style="list-style-type: none"> ● 400V plug ● 230V plug ● Earthing kit | | <ul style="list-style-type: none"> ● Automatic transfer unit (AMF) EAS 17-805 ● Remote control ● Tank locking cap | | | | <ul style="list-style-type: none"> ● Site tow CTL400 ● Road trolley CTV4 | | | | |
| | <ul style="list-style-type: none"> ● Oil heater OH | | | | | | | | | | |

Technische gegevens

GE 15000 SC GE 15000 SXC GE 15000 SXC EAS

| | |
|---|---|
| A.C GENERATOR – 50 Hz | Three-phase asynchronous alternator, self-excited, self-regulated, brushless |
| * Stand-by three-phase power | 16.5 kVA (13.2 kW) / 400 V / 23.8 A |
| * P.R.P. three-phase power | 15 kVA (12 kW) / 400 V / 21.7 A |
| * P.R.P. single-phase power | 10 kVA / 230 V / 43.5 A |
| Cos φ | 0.8 |
| Insulation class | H |
| * Output powers according to ISO 8528-1 | |

| | |
|----------------------------------|--|
| MOTOR | 4-stroke diesel, air cooled, direct injection |
| Model | Lombardini 9LD625/2 |
| * Stand-By net power | 18.8 kW (25.5 HP) |
| * P.R.P. net power | 17.1 kW (23.2 HP) |
| Cylinders/ Displacement | 2/ 1248 cm ³ |
| Speed | 3000 rpm |
| Fuel consumption (75% of P.R.P.) | 3.5 l/h |
| * Powers according to ISO 3046-1 | |

| | |
|---|---------------------------|
| ALGEMENE SPECIFICATIES | |
| Tank capacity | 26 l |
| Running time (75% of P.R.P.) | 7.5 h |
| IP protection degree | IP 23 |
| *Dimensions LxWxh (mm) | 1455x870x880 |
| *Dry weight | 386 kg |
| **Measured acoustic power LwA (pressure LpA) | 406 kg |
| **Guaranteed acoustic power LwA (pressure LpA) | 96 dB(A) (71 dB(A) @ 7 m) |
| ***Acoustic power LwA (pressure LpA) | 96 dB(A) (71 dB(A) @ 7 m) |
| | 98 dB(A) (73 dB(A) @ 7 m) |
| * Dimensions and weight without trolley/trailer. ** Acoustic power according to European Directive 2000/14/EC | |
| ***For indoor use / For fixed installation only, in compliance with Directive 2000/14/EC | |

Model- en specificatiewijzigingen voorbehouden