

# STROOMAGGREGAAT GE 3000 SX

- Honda OHV benzinemotor
- Oliëniveaubeveiliging
- Enkelfase synchrone generator
- Uitgangen: 1 x 230V 16A 2P+T CEE  
1 x 230V 16A 2P+T SCHUKO
- ELCB-GFI (aardlekschakelaar)
- Thermische beveiliging tegen overbelasting
- Geschikt voor o.a. electronische apparatuur
- Beschermende omkasting
- Geluidgedempt
- Draagbaar
- Voldoet aan de EG veiligheids- en geluidsnormen



Standaard uitrusting										
	Petrol engine	Air cooling	Manual recoil	Oil alert	Engine shut down (oil)					
	Synchronous alternator	Sockets	ELCB-GFI	Thermal shut off	Battery charger					
Opties	● 230V Plug		● Earthing kit							

## Technische gegevens

## GE 3000 SX

<b>A.C. GENERATOR- 50 Hz</b>	<b>Single-phase synchronous alternator, self-excited, self-regulated, brushless</b>
* Stand-by single-phase power	2.8 kVA (2.5 kW) / 230 V / 12.2 A
* P.R.P. single-phase power	2.1 kVA (1.9 kW) / 230 V / 9.1 A
Cos φ	0.9
Battery charger	12Vd.c. - 10A
Insulation class	H
* Output powers according to ISO 8528-1	
<b>MOTOR</b>	<b>4-stroke petrol, air cooled, OHV</b>
Model	Honda GX 160
* Stand-By net power	3.3 kW (4.5 HP)
* P.R.P. net power	2.5 kW (3.4 HP)
Cylinders/ Displacement	1/ 163 cm <sup>3</sup>
Speed	3000 rpm
Fuel consumption (75% of P.R.P)	0.9 l/h
* Powers according to SAE J1349	
<b>ALGEMENE SPECIFICATIES</b>	
Tank capacity	3.1 l
Running time (75% of P.R.P)	3.5 h
IP protection degree	IP 23
Dimensions LxWxh (mm)	570x420x450 mm
Dry weight	50 kg
*Measured acoustic power LwA (pressure LpA)	94 dB(A)(69 dB(A) @ 7m)
*Guaranteed acoustic power LwA (pressure LpA)	95 dB(A)(70 dB(A) @ 7m)
* Acoustic power according to European Directive 2000/14/EC	