

## STROOMAGGREGAAT GE 4500 SX - GE 4500 E/SX - GE 4500 SX EAS

- Honda OHV benzinemotor
- Oliëniveaubewakingl
- Enkelfase synchrone generator
- Uitgangen: 2 x 230V 16A 2P+T CEE
- ELCB-GFI (aardlekschakelaar)
- Thermische beveiliging tegen overbelasting
- Geschikt voor electronische apparatuur
- Beschermende omkasting
- Geluidgedempt
- Draagbaar
- Ideaal voor servicewagen en aannemerij
- Voldoet aan EG veiligheids- en geluidsnormen



Standaard Uitrusting								* Only E/SX - SX EAS ** Only SX *** Only SX EAS		
	Petrol engine	Air cooling	Manual Recoil **	Electric Starter *	Battery 12 V *	Oil alert	Engine shut down (oil)			
Opties										
	Synchronous alternator	Sockets	ELCB-GFI	Thermal shut off	Battery charger	Ready for EAS/TCM ***	Local/remote start selector ***			
Uitvoering op verzoek										

Technische gegevens	GE 4500 SX Recoil start	GE 4500 E/SX Electric start	GE 4500 SX EAS For use with EAS
<b>A.C GENERATOR – 50 Hz</b>	Single-phase synchronous alternator, self-excited, self-regulated, brushless		
* Stand-by single-phase power		4.9 kVA (4.4 kW) / 230 V / 21.3 A	
* P.R.P. single-phase power		4 kVA (3.6 kW) / 230 V / 17.4 A	
Cos φ		0.9	
Battery charger		12Vd.c. - 10A	
Insulation class		H	
* Output powers according to ISO 8528-1			
<b>MOTOR</b>	4-stroke petrol, air cooled, OHV		
Model		Honda GX 270	
* Stand-By net power		5.7 kW (7.7 HP)	
* P.R.P. net power		4.6 kW (6.2 HP)	
Cylinders/ Displacement		1/ 270 cm <sup>3</sup>	
Speed		3000 rpm	
Fuel consumption (75% of P.R.P.)		1.7 l/h	
* Powers according to SAE J1349			
<b>ALGEMENE SPECIFICATIES</b>			
Tank capacity		5.3 l	
Running time (75% of P.R.P.)		3.1 h	
IP protection degree		IP 23	
Dimensions LxWxh (mm)		660x495x525 mm	
Dry weight	73 Kg		78 Kg
*Measured acoustic power LwA (pressure LpA)		96 dB(A) (71 dB(A) @ 7m)	
*Guaranteed acoustic power LwA (pressure LpA)		97 dB(A) (72 dB(A) @ 7m)	
* Acoustic power according to European Directive 2000/14/EC			

Model- en specificatiewijzigingen voorbehouden