

STROOMAGGREGAAT GE 6000 SX/GS EAS

- Yanmar dieselmotor
- EV motorbewaking
- Elektrische start
- Enkelfase synchrone generator
- Uitgangen: 1 x 230V 32A 2P+T CEE - 1 x 230V 16A 2P+T CEE
- ELCB-GFI (Aardlekschakelaar)
Zekeringautomaat
- Super geluidgedempt
- Onderstel (option)
- Voorbereid voor noodstroom/start-stop op afstand
- Voldoet aan EG veiligheids- en geluidseisen
- Compact, stil en robuust
- Betaalbare topkwaliteit, ideaal voor aannemerij



Standaard uitrusting										
	Diesel engine	Air cooling	Electric Starter	Battery 12 V	Engine protection	Oil pressure shut down	Low fuel shut down	Battery charge indicator	Hour-meter	Central lifting eye
Opties										
	Synchronous alternator	Sockets	ELCB-GFI	Circuit Breaker	Thermal shut off	Voltmeter	Ready for EAS/TCM	Local/remote start selector		
	<ul style="list-style-type: none"> ● 230V plugs ● 115V plugs 				<ul style="list-style-type: none"> ● Remote control ● Automatic transfer unit (AMF) EAS 15D-806 ● Earthing kit 				<ul style="list-style-type: none"> ● Exhaust extension ● Trolley CTM2 ● Road trolley CTV4 	

Technische gegevens

GE 6000 SX/GS EAS

A.C GENERATOR – 50 Hz

- * Stand-by single-phase power (230V)
- * P.R.P. single-phase power (230V)
- * Stand-by single-phase power (115V)
- * P.R.P. single-phase power (115V)
- Cos φ
- Insulation class

* Output powers according to ISO 8528-1

Single-phase synchronous alternator, self-excited, self-regulated, brushless

- 5.7 kVA (5.1 kW) / 230 V / 24.8 A
- 5 kVA (4.5 kW) / 230 V / 21.7 A
- 5.7 kVA (6 kW) / 115 V / 49.6 A
- 5 kVA (5 kW) / 115 V / 43.5 A
- 0.9
- H

MOTOR

4-stroke diesel, air cooled, direct injection

- Model Yanmar L 100 N
- * Stand-By net power 6.5 kW (8.8 HP)
- * P.R.P. net power 5.7 kW (7.7 HP)
- Cylinders/ Displacement 1/ 435 cm³
- Speed 3000 rpm
- Fuel consumption (75% of P.R.P.) 1.2 l/h

* Powers according to ISO 3046-1

ALGEMENE SPECIFICATIES

- Tank capacity 23 l
 - Running time (75% of P.R.P.) 19 h
 - IP protection degree IP 23
 - *Dimensions LxWxh (mm) 1020x645x930 mm
 - *Dry weight 194 kg
 - **Measured acoustic LwA (pressure LpA) 92 dB(A) (67 dB(A) @ 7m)
 - **Guaranteed acoustic LwA (pressure LpA) 93 dB(A) (68 dB(A) @ 7m)
- * Dimensions and weight without trolley/trailer. ** Acoustic power according to European Directive 2000/14/EC