

## STROOMAGGREGAAT GE 6500 SX/GS EAS

- Yanmar dieselmotor
- EV motorbewaking
- Electric start
- Enkelfase synchrone generator
- Uitgangen: 1 x 400V 16A 3P+N+T CEE  
1 x 230V 16A 2P+T CEE
- ELCB-GFI (aardlekschakelaar)
- Zekeringautomaat
- Super geluidgedempt
- Onderstel (optie)
- Compact, stil en robuust
- Betaalbare topkwaliteit, ideaal voor aannemerij



Standaard Uitrusting										
	Diesel engine	Air cooling	Electric starter	Battery 12 V	Engine protection	Oil pressure shut down	Low fuel shut down	Battery charge indicator	Hour-meter	Central lifting eye
Opties										
	Synchronous alternator	Compound	Sockets 3~	Sockets 1~	ELCB-GFI	Circuit Breaker	Voltmeter	Ready for EAS/TCM	Local/remote start selector	

- |                   |  |   |  |
|-------------------|--|---|--|
| <b>Opties</b><br> | <ul style="list-style-type: none"> <li>● 400V plug</li> <li>● 230V plug</li> </ul> | <ul style="list-style-type: none"> <li>● Automatic transfer unit (AMF) EAS 15D-806</li> <li>● Remote control</li> <li>● Earthing kit</li> </ul> | <ul style="list-style-type: none"> <li>● Exhaust extension</li> <li>● Trolley CTM2</li> <li>● Road trolley CTV4</li> </ul> |
|-------------------|--|---|--|

- Uitvoering op verzoek**
- Schuko socket

### Technische gegevens

### GE 6500 SX/GS EAS

<b>A.C GENERATOR – 50 Hz</b>	<b>Three-phase synchronous alternator, self-excited, self-regulated</b>
------------------------------	---

<ul style="list-style-type: none"> <li>* Stand-by three-phase power</li> <li>* P.R.P. three-phase power</li> <li>* P.R.P. single-phase power</li> </ul>	<ul style="list-style-type: none"> <li>6.5 kVA (5.2 kW) / 400 V / 9.4 A</li> <li>5.7 kVA (4.6 kW) / 400 V / 8.2 A</li> <li>4 kVA / 230 V / 17.4 A</li> </ul>
<b>Cos φ</b>	0.8
<b>Insulation class</b>	H
* Output powers according to ISO 8528-1	

<b>MOTOR</b>	<b>4-stroke diesel, air cooled, direct injection</b>
--------------	--

<ul style="list-style-type: none"> <li><b>Model</b></li> <li>* Stand-By net power</li> <li>* P.R.P. net power</li> </ul>	<ul style="list-style-type: none"> <li>Yanmar L 100 N</li> <li>6.5 kW (8.8 HP)</li> <li>5.7 kW (7.7 HP)</li> </ul>
<b>Cylinders/ Displacement</b>	1/435 cm <sup>3</sup>
<b>Speed</b>	3000 rpm
<b>Fuel consumption (75% of P.R.P.)</b>	1.2 l/h
* Powers according to ISO 3046-1	

### ALGEMENE SPECIFICATIES

<ul style="list-style-type: none"> <li><b>Tank capacity</b></li> <li><b>Running time (75% of P.R.P.)</b></li> <li><b>IP protection degree</b></li> <li>* <b>Dimensions LxWxh (mm)</b></li> <li>* <b>Dry weight</b></li> <li>** <b>Measured acoustic power LwA (pressure LpA)</b></li> <li>** <b>Guaranteed acoustic power LwA (pressure LpA)</b></li> </ul>	<ul style="list-style-type: none"> <li>23 l</li> <li>19 h</li> <li>IP 23</li> <li>1020x645x930 mm</li> <li>200 kg</li> <li>91 dB(A) (66 dB(A) @ 7m)</li> <li>92 dB(A) (67 dB(A) @ 7m)</li> </ul>
* Dimensions and weight without trolley/trailer. ** Acoustic power according to European Directive 2000/14/EC	