

STROOMAGGREGAAT GE 145 JSX EAS - GE 145 JMSX EAS

- JCB watergekoelde dieselmotor - 1500 rpm
- EP6 motorbeveiliging
- GE 145 JSX – STAMFORD driefase synchrone generator
- GE 145 JMSX – MARELLI driefase synchrone generator
- 4 polige hoofdschakelaar
- Super geluïdgedempt
- Carter aftappomp
- Lekbak
- Onderstel (optie)
- Voorbereid voor noodstroom / start-stop op afstand
- Robuuste, compacte machinel



Standaard uitvoering											
	Diesel engine	Water cooling	Battery 12V	Fuel level gauge	Engine protection	Electric Starter	low press. shut down	high water shut down	over speed shut down	low fuel Shut down	battery charge alarm
						Rpm-meter	Hours-meter	Battery Voltmeter	Voltmeter	Frequency-meter	Remote start
Opties af fabriek											
	Synchronous alternator	Automatic Voltage Regulator	Circuit Breaker	Terminal block	Ammeter	Voltmeter phase selector	Emergency stop button	Siren	Ready for EAS/TCM	Central lifting eye	Warning lamp Water in fuel

- Electrical panel with sockets :1x400V 125A 3P+N+T CEE - 1x400V 63A 3P+N+T CEE - 1x400V 32A 3P+N+T CEE - 1x400V 16A 3P+N+T CEE - 2 x 230V 16A 2P+T CEE
- The electrical panel requires an electrical protection : ELR-Earth Leakage Relay (GFI) or Isometer (Insulation monitors)
- ELR-Earth Leakage Relay (GFI)
- Isometer (Insulation monitors)
- Volt adjustable from control panel
- Radio-control
- Gauges – water temperature and oil pressure
- Water heater WH
- Automatic fuel transfer pump
- Permanent Magnet Generator
- Fuel tank 120l
- Fuel tank 350l
- 3-way valve fuel system with quick connection for external fuel tank feeding

- Opties
 - 400 plugs
 - 230 plugs
 - Automatic transfer unit (AMF) EAS 170-805
 - Remote control TCM35
 - Earthing kit
 - Site tow CTL115
- Uit. op verzoek
 - 24 h autonomy version

Technische gegevens

A.C GENERATOR – 50 Hz	GE 145 JSX EAS	GE 145 JMSX EAS
	Three-phase synchronous alternator, self-excited, self-regulated, brushless	
* Stand-by three-phase power	140 kVA (112 kW) / 400 V / 202 A	
* P.R.P. three-phase power	127 kVA (102 kW) / 400 V / 183 A	
* P.R.P. single-phase power	45 kVA / 230 V / 196A	
Cos φ	0.8	
Insulation class	H	

MOTOR

	4-stroke diesel, turbocharged , direct injection, water cooled
Model	JCB 448 G-TCA
* Stand-By net power	122 kW (166 HP)
* P.R.P. net power	110 kW (150 HP)
Cylinders/ Displacement	4.8 l (4800 cm ³)
Speed	1500 rpm.
Fuel consumption (75% of P.R.P.)	22.4 l/h

ALGEMENE SPECIFICATIES

Tank capacity	230 l
Running time (75% of P.R.P.)	103 h
IP protection degree	IP 44
*Dimensions LxWxh (mm)	2820x1200x1820
*Dry weight	2020 kg
**Measured acoustic power LwA (pressure LpA)	94 dB(A) (69 dB(A) @ 7 m)
**Guaranteed acoustic power LwA (pressure LpA)	95 dB(A) (70 dB(A) @ 7 m)

* Dimensions and weight without trolley/trailer. **Acoustic power according to European Directive 2000/14/EC