

STROOMAGGREGAAT GE 65 JSX EAS - GE 65 JMSX EAS

- JCB watergekoelde dieselmotor - 1500 rpm
- EP6 motorbeveiliging
- GE 65 JSX – STAMFORD driefase synchrone generator
- GE 65 JSMX – MARELLI driefase synchrone generator
- 4 polige hoofdschakelaar
- Super geluidgedempt
- Carteraftappomp
- Lekbak
- Onderstel (optie)
- Voorbereid voor noodstroom / start-stop op afstand
- Robuuste machine, flinke tankinhoud



Standaard uitvoering											

- Opties af fabriek**
- Electrical panel with sockets :1x400V 125A 3P+N+T CEE - 1x400V 63A 3P+N+T CEE - 1x400V 32A 3P+N+T CEE - 1x400V 16A 3P+N+T CEE - 2 x 230V 16A 2P+T CEE
 - The electrical panel requires an electrical protection : ELR-Earth Leakage Relay (GFI) or Isometer (Insulation monitors)
 - ELR-Earth Leakage Relay (GFI)
 - Isometer (Insulation monitors)
 - Volt adjustable from control panel
 - Radio-control
 - Gauges – water temperature and oil pressure
 - Water heater WH
 - Automatic fuel transfer pump
 - Permanent Magnet Generator only with Stamford alternator
 - Fuel tank 120l
 - Fuel tank 350l
 - 3-way valve fuel system with quick connection for external fuel tank feeding

- Opties**
- 400 plugs
 - 230 plugs
 - Automatic transfer unit (AMF) EAS 76-805
 - Remote control TCM35
 - Earthing kit
 - Site tow CTL115
- Uitvoering op verzoek**
- 24 h autonomy version

Technische gegevens

	GE 65 JSX EAS	GE 65 JMSX EAS
--	---------------	----------------

A.C GENERATOR – 50 Hz	Three-phase synchronous alternator, self-excited, self-regulated, brushless	
* Stand-by three-phase power	66 kVA (52.8 kW) / 400 V / 95.2 A	
* P.R.P. three-phase power	60 kVA (48 kW) / 400 V / 86.7 A	
* P.R.P. single-phase power	22 kVA / 230 V / 95.2 A	
Cos φ	0.8	
Insulation class	H	

MOTOR	4-stroke diesel, turbocharged , direct injection, water cooled	
Model	JCB 444 G-TC1	
* Stand-By net power	58.9 kW (80.1 HP)	
* P.R.P. net power	52.9 kW (72 HP)	
Cylinders/ Displacement	4/ 4.4 l (4400 cm ³)	
Speed	1500 rpm	
Fuel consumption (75% of P.R.P.)	10.6 l/h	

ALGEMENE SPECIFICATIES		
Tank capacity	230 l	
Running time (75% of P.R.P.)	21.5 h	
IP protection degree	IP 44	
*Dimensions LxWxh (mm)	2740x1200x1720	
*Dry weight	1700 kg	1630 kg
**Measured acoustic power LwA (pressure LpA)	95 dB(A) (70 dB(A) @ 7 m)	
**Guaranteed acoustic power LwA (pressure LpA)	96 dB(A) (71 dB(A) @ 7 m)	

* Dimensions and weight without trolley/trailer. **Acoustic power according to European Directive 2000/14/EC