

STROOMAGGREGAAT GE 10000 DS/GS

- Luchtgekoelde dieselmotor - 3000 rpm
- Elektrische start incl. accu
- Driefase synchrone generator
- Uitgangen: 1 x 400V 16A 3P+N+T CEE
1 x 230V 32A 2P+T CEE - 1 x 230V 16A 2P+T randaarde.
- ELCB-GFI (aardlekschakelaar)
- Zekeringautomaat
- Buizenframe
- Onderstel (optie)
- Voldoet aan de EG veiligheids- en geluidsnormen



Standaard uitrusting										
	Diesel engine	Air cooling	Electric Starter	Battery 12V	Oil pressure Indicator	Battery charge indicator	Hour-meter			
	Synchronous alternator	Compound	Sockets 3~	Sockets 1~	ELCB-GFI	Circuit Breaker	Thermal shut off	Voltmeter		
Opties	● 400V plug ● 230V plug		● Earthing kit				● Trolley CTM10			

Technische gegevens

GE 10000 DS/GS

A.C GENERATOR – 50 Hz

Three-phase synchronous alternator, self-excited, self-regulated

* Stand-by three-phase power	11 kVA (8.8 kW) / 400 V / 15.9 A
* P.R.P. three-phase power	10 kVA (8 kW) / 400 V / 14.4 A
* P.R.P. single-phase power	6 kVA / 230 V / 26 A
Cos φ	0.8
Insulation class	H

* Output powers according to ISO 8528-1

MOTOR

4-stroke diesel, air cooled, direct injection

Model	Lombardini 25LD 425/2
* Stand-by net power	11.5 kW (15.6 HP)
* P.R.P. net power	10.5 kW (14.3 HP)
Cylinders/ Displacement	2/ 851 cm ³
Speed	3000 rpm
Fuel consumption (75% of P.R.P.)	2.2 l/h

* Powers according to ISO 3046-1

ALGEMENE SPECIFICATIES

Tank capacity	18 l
Running time (75% of P.R.P.)	8.2 h
IP protection degree	IP 23
*Dimensions LxWxh (mm)	910x580x620 mm
*Dry weight	153 kg
**Acoustic power LwA (pressure LpA)	99 dB(A) (74 dB(A) @ 7m)

* Dimensions and weight without trolley/trailer. ** For indoor use / For fixed installation only, in compliance with Directive 2000/14/EC