

STROOMAGGREGAAT GE 12000 LD/GS

- Lombardini luchtgekoelde dieselmotor
- Elektrische start
- Driefase synchrone generator
- Uitgangen: 1 x 400V 32A 3P+N+T CEE
1 x 230V 32A 2P+T CEE - 1 x 230V 16A 2P+T SCHUKO
- ELCB-GFI (aardlekschakelaar)
- Circuit breaker
- Beschermend buizenframe
- Onderstel (optie)
- Voldoet aan EG geluids- en veiligheidsnormen



Standaard uitrusting										
	Diesel engine	Air cooling	Electric Starter	Battery 12V	Oil pressure Indicator	Battery charge indicator	Hour-meter			
	Synchronous alternator	Compound	Sockets 3~	Sockets 1~	ELCB-GFI	Circuit Breaker	Thermal shut off	Voltmeter		
Opties	<ul style="list-style-type: none"> ● 400V plug ● 230V plug 		<ul style="list-style-type: none"> ● Earthing kit 				<ul style="list-style-type: none"> ● Trolley CTM10 			

Technische gegevens

GE 12000 LD/GS

A.C GENERATOR – 50 Hz

Three-phase synchronous alternator, self-excited, self-regulated

* Stand-by three-phase power
* PRP three-phase power
* PRP single-phase power
Cos φ
Insulation class

12 kVA (9.6 kW) / 400 V / 17.3 A
11 kVA (8.8 kW) / 400 V / 15.9 A
6 kVA / 230 V / 26 A
0.8
H

* Output powers according to ISO 8528-1

MOTOR

4-stroke diesel, air cooled, direct injection

Model
* Stand-by net power
* P.R.P. net power
Cylinders/ Displacement
Speed
Fuel consumption (75% of PRP)

Lombardini 25LD 425/2
11.5 kW (15.6 HP)
10.5 kW (14.3 HP)
2/ 851 cm³
3000 rpm
2.2 l/h

* Powers according to ISO 3046-1

ALGEMENE SPECIFICATIES

Tank capacity
Running time (75% of PRP)
IP protection degree
*Dimensions LxWxh (mm)
*Dry weight
**Acoustic power LwA (pressure LpA)

18 l
8.2 h
IP 23
935x580x645
156 kg
99 dB(A) (74 dB(A) @ 7m)

* Dimensions and weight without trolley/trailer. ** For indoor use / For fixed installation only, in compliance with Directive 2000/14/EC