MOSA ISO 9001:2000 - Cert. 0192

# STROOMAGGREGAAT
# GE 6000 DS/GS - DES/GS

- Yanmar dieselmotor
- Handstart (DS/GS)
- Electrische start (DES/GS)
- Enkelfase synchrone generator
- Wandkontakdozen: 1 x 230V 32A 2P+T CEE
  1 x 230V 16A 2P+T CEE
- ELCB-GFI (aardlekschakelaar)
- Zekeringautomaat
- Buizenframe
- Onderstel (optie)
- Voldoet aan de EG veiligheids- en geluidsnormen

**Standaard Uitrusting**

| | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|
| Diesel engine | Air cooling | Manual recoil ** | Electric Starter * | Oil pressure Indicator * | Battery * charge indicator | Hour-meter | | | * only DES/GS<br>** only DS/GS | |
| Synchronous alternator | Sockets | ELCB-GFI | Circuit Breaker | Thermal shut off | Voltmeter | | | | | |

**Opties**

- 230V plug
- Earthing kit
- Battery holder complete with battery
- Trolley CTM6/2

**Uitvoering op verzoek**

- Schuko sockets

## Technische gegevens

| | GE 6000 DS/GS | GE 6000 DES/GS |
|---|---|---|
| **A.C GENERATOR – 50 Hz** | **Single-phase synchronous alternator,self-excited, self-regulated, brushless** | |
| *** Stand-by single-phase power (230V)** | 5.7 kVA (5.1 KW) / 230 V / 24.8 A | |
| *** P.R.P. single-phase power (230V)** | 5 kVA (4.5 KW) / 230 V / 21.7 A | |
| ***1 Stand-by single-phase power (115V)** | 5.7 kVA (6 kW) / 115 V / 49.6 A | |
| ***1 P.R.P. single-phase power (115V)** | 5 kVA (5 kW) / 115 V / 43.5 A | |
| **Cos φ** | 0.9 | |
| **Insulation class** | H | |
| * Output powers according to ISO 8528-1 | | |
| **MOTOR** | **4-stroke diesel, air cooled, direct injection** | |
| **Model** | Yanmar L 100 N | |
| *** Stand-By net power** | 6.5 kW (8.8 HP) | |
| *** P.R.P. net power** | 5.7 kW (7.7 HP) | |
| **Cylinders/ Displacement** | 1/ 435 $cm^3$ | |
| **Speed** | 3000 rpm | |
| **Fuel consumption (75% of P.R.P.)** | 1.2 l/h | |
| * Powers according to ISO 3046-1 | | |
| **ALGEMENE SPECIFICATIES** | | |
| **Tank capacity** | 5.5 l | |
| **Running time (75% of P.R.P.)** | 4.6 h | |
| **IP protection degree** | IP 23 | |
| ***Dimensions LxWxh (mm)** | 900x550x622 | |
| ***Dry weight** | 96 Kg | 97 Kg |
| ****Acoustic power LwA (pressure LpA)** | 99 dB(A) (74 dB(A) @ 7m) | |

* Dimensions and weight without trolley/trailer ** For indoor use / For fixed installation only, in compliance with Directive 2000/14/EC

**Model- en specificatiewijzigingen voorbehouden**


MOSA Aggregaten B.V. - Watermolen 4b - 4751 VK Oud Gastel tel 0165-518672 fax 0165-518682 www.mosa-aggregaten.nl