

STROOMAGGREGAAT GE 6500 DS/GS - DES/GS

- Yanmar dieselmotor
- Handstart (DS/GS)
- Elektrische start (DES/GS)
- Driefase synchrone generator
- Uitgangen: 1 x 400V 16A 3P+N+T CEE
1 x 230V 16A 2P+T CEE
- ELCB-GFI (aardlekschakelaar)
- Zekeringautomaat
- Buizenframe
- Onderstel (optie)
- Voldoet aan EG veiligheids- en geluidsnormen



Standaard Uitrusting										
	Diesel engine	Air cooling	Manual recoil **	Electric Starter *	Oil pressure Indicator *	Battery charge indicator *	Hour-meter			
	Opties									
		● 400V plug ● 230V plug			● Earthing kit					
									● Battery holder complete with battery ● Trolley CTM6/2	

* only GE6500 DES/GS
** only GE6500 DS/GS

Uitvoering op verzoek

- Schuko sockets

Technische gegevens

GE 6500 DS/GS

GE 6500 DES/GS

A.C GENERATOR – 50 Hz

Three-phase synchronous alternator, self-excited, self-regulated

* Stand-by three-phase power

* P.R.P. three-phase power

* P.R.P. single-phase power

Cos φ

Insulation class

* Output powers according to ISO 8528-1

6.5 kVA (5.2 kW) / 400 V / 9.4 A

5.7 kVA (4.6 kW) / 400 V / 8.2 A

4 kVA / 230 V / 17.4 A

0.8

H

MOTOR

4-stroke diesel, air cooled, direct injection

Model

* Stand-By net power

* P.R.P. net power

Cylinders/ Displacement

Speed

Fuel consumption (75% of P.R.P.)

* Powers according to ISO 3046-1

Yanmar L100N

6.5 kW (8.8 HP)

5.7 kW (7.7 HP)

1/ 435 cm³

3000 rpm

1.2 l/h

ALGEMENE SPECIFICATIES

Tank capacity

Running time (75% of P.R.P.)

IP protection degree

*Dimensions LxWxh (mm)

*Dry weight

** Acoustic power LwA (pressure LpA)

* Dimensions and weight without trolley/trailer. ** For indoor use / For fixed installation only, in compliance with Directive 2000/14/EC

5.5 l

4.6 h

IP 23

900x550x622 mm

107 Kg

99 dB(A) (74 dB(A) @ 7m)

108 Kg