

STROOMAGGREGAAT GE 8000 DS/GS

- Luchtgekoelde dieselmotor - 3000 rpm
- Elektrische start incl. accu
- Enkelfase synchrone generator
- Uitgangen : 1 x 230V 32A 2P+T CEE
1 x 230V 16A 2P+T CEE
- ELCB-GFI (aardlekschakelaar)
- Zekeringautomaat
- Geschikt voor o.a. elektronische apparatuur
- Buizenframe
- Onderstel (optie)
- Voldoet aan de EG veiligheids- en geluidsnormen



Standaard Uitrusting										
	Diesel engine	Air cooling	Electric Starter	Battery 12V	Oil pressure Indicator	Battery charge indicator	Hour-meter			
	Synchronous alternator	Sockets	ELCB-GFI	Circuit Breaker	Thermal shut off	Voltmeter				
Opties	● 230v plugs			● Earthing kit			● Trolley CTM10			

Technische gegevens

GE 8000 DS/GS

A.C GENERATOR – 50 Hz	Single-phase synchronous alternator, self-excited, self-regulated, brushless
* Stand-by single-phase power	9 kVA (8.1 kW) / 230 V / 39.1 A
* P.R.P. single-phase power	8 kVA (7.2 kW) / 230 V / 34.8 A
Cosφ	0.9
Insulation class	H
* Output powers according to ISO 8528-1	
MOTOR	4-stroke diesel, air cooled, direct injection
Model	Lombardini 25LD 425/2
* Stand-By net power	11.5 kW (15.6 HP)
* P.R.P. net power	10.5 kW (14.3 HP)
Cylinders/ Displacement	2/ 851 cm ³
Speed	3000 rpm
Fuel consumption (75% of P.R.P)	2.2 l/h
* Powers according to ISO 3046-1	
ALGEMENE SPECIFICATIES	
Tank capacity	18 l
Running time (75% of P.R.P)	8.2 h
IP protection degree	IP 23
*Dimensions LxWxh (mm)	910x580x620 mm
*Dry weight	140 kg
**Acoustic power LwA (pressure LpA)	99 dB(A)(74 dB(A) @ 7m)
* Dimensions and weight without trolley/trailer. ** For indoor use / For fixed installation only, in compliance with Directive 2000/14/EC	